



# FALCON FAMILY

MOTION SENSOR FOR INDUSTRIAL DOORS,  
GATES & WARNING INDICATION

## VIDEO



[Watch the product video](#)

## TECHNOLOGY



## CERTIFICATIONS




## DESCRIPTION

BEA's **FALCON FAMILY** of sensors is the premier microwave activation solution for indoor and outdoor industrial applications. The family includes the **FALCON**, **FALCON XL** (extra low mount) and **FALCON WIDE** (for wide detection areas).


The sensor is capable of providing pedestrian and parallel traffic rejection, reducing unwanted detections and door cycles.

BEA's **FALCON FAMILY** is ideal for automatic industrial doors, vehicle gates / barriers, vehicle detection, loading docks or any other industrial application where motion detection is required.


Housed in a IP65 rated enclosure, the **FALCON FAMILY** is designed to operate in harsh environments.




**H=11' / Tilt Angle=30**



**H = 16' / Tilt Angle = 30**  
*(Standard FALCON Pattern)*



**H = 8' / Tilt Angle = 30**  
*(FALCON XL Pattern)*



**H = 11.5' / Sensitivity = 9**  
*(FALCON Wide Pattern)*

## Energy Savings

Bidirectional, unidirectional approach and unidirectional depart microwave detection options

## Adjustable Detection Settings

Six modes of detection filtering for pedestrian and parallel traffic rejection

## Remote Control Adjustments

Remote control programming enables user to quickly and safely make changes from the ground


## Adjustable Angle

Tilt angle from 0 to 180°


## Rated For Harsh Environments

IP65 rated enclosure


## APPLICATIONS




Factory Entrances



Pedestrian & Parallel Traffic Rejection



Parking Garage Detection



Barrier Arm Activation

## TECHNICAL SPECIFICATIONS

<b>Technology</b>	Microwave Doppler Radar
Radiated Frequency	24.150 GHz
Transmitter Radiated Frequency	< 20 dBm EIRP
Radiated Power Density	< 5 mW / cm <sup>2</sup>
<b>Detection Mode</b>	Motion
<b>Detection Zone</b>	
FALCON	13' x 16' @ 16'
FALCON XL	13' x 6 1/2' @ 8 1/2'
FALCON WIDE	30' x 11' @ 21'
	Typical at 30° and field size 9
<b>Tilt Angles</b>	0 – 180°
<b>Output</b>	Relay (free of potential change-over contact)
Max. Contact Voltage	42 VAC / VDC
Max. Contact Current	1 A (resistive)
Max. Switching Power	30 W (DC); 60 VA (AC)
<b>Minimum Detection Speed</b>	2 in / s*
<b>Mains Frequency</b>	50 – 60 Hz
<b>Supply Voltage</b>	12 – 24 VAC; ±10% 12 – 24 VDC; 30% / -10%
<b>Power Consumption</b>	< 2 W
<b>Mounting Height</b>	
FALCON	11 1/2 – 23'
FALCON XL	6 1/2 – 11 1/2'
FALCON WIDE	11 1/2 – 21'
<b>Dimensions</b>	3 3/4" (W) x 4" (H) x 5" (L)
<b>Material</b>	ABS & Polycarbonate
<b>Temperature Range</b>	-22 – 140 °F
<b>Degree of Protection</b>	IP65
<b>Norm Conformity</b>	EMC: 2004 / 108 / EC R&TTE: 1999 / 5 / EC

\*Measured in optimal conditions

## PRODUCT SERIES



**10FALCON**  
Standard mounting heights




**10FALCONXL**  
Low mounting heights



**10FALCONW**  
Wide detection fields



**10FALCONEX**  
Explosion proof motion sensor series



**10INDBRACKET**  
Adjustable mounting bracket



**10MINIBRACKET**  
Short adjustable mounting bracket



**10REMOT**  
BEA universal remote control



**10WBA**  
Universal mounting bracket arm



**10WBAMOUNT**  
Universal mounting bracket plate

**DISCLAIMER** Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

[WWW.BEASENSORS.COM](http://WWW.BEASENSORS.COM)



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA  
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company